



E-Brake C 200T Ultra with Tool Mate

Specifications

SafanDarley E-Brake Ultra basic version NS

- EC20 Control
 - Dual touch screen on swivel arm, height adjustable
 - EC Profiler 2D bending simulation with automatic bending sequence calculation
 - Viewer for AutoPOL, Radan and Metalix graphic files
- Y1/Y2 axis, CNC controlled
- X-axis, CNC controlled
- R-axis, CNC controlled
- Z1 & Z2 axls, type H, CNC programmable lateral adjustment of the backgauge fingers, independently adjustable
- Backgauge dX-axis adjustment. Type H. Stroke 200 mm (+/- 100 mm.), on Z2, incl. 3D inserts
- AKAS 5PM, CNC programmable
- NSCL-II HC Premium. Top tool adapter with hydraulic clamping, with hardened surfaces. incl. hydraulic unit
- NSCR-II HC Premium. CNC controlled crowning system with hydraulic lower tool clamping. incl. V-Lock
- E-Bend L Blue Angle Measuring System
- Swivel arm detection sensor
- Tool lighting at the front
- 2 movable support arms (stainless steel) with lateral T-slots
- 2 stop cams for E 200-4300: Q size 690mm
- Tool Mate 32, 52 or 60 metre tool storage capacity