

NBH 630

+ Available from September 2024 +

Stable. Powerful. Flexible.

Highlights

- **70 m/min** rapid traverse in all axes,
- Dynamic motor spindle with 8,000 rpm,
- Pallet size of 630 x 630 mm,
- Max. pallet loading of 1,500 kg,
- Hydraulic clamping 6-fold with 240 bar,
- Prepared for integration in any automation,
- Delivery, installation and 24 months warranty inclusive.



Specification

_	Basic machine NBH 630	incl.
_	Motor spindle wit 8,000 rpm, HSK-A 100, 66 kW/370 Nm (at 40 % DC)	incl.
_	NC rotary table (torque drive) with hydraulic clamping 6-fold, 240 bar hydraulic pressure	incl.
_	180° pallet changer, 2 pallets 630 x 630 mm with tapped holes	incl.
_	Automatic loading door at set-up station for automation	incl.
_	Tool disc magazine with 60 locations	incl.
_	Tool breakage control, preparation infrared measuring probe for brand Renishaw	incl.
_	Scraper belt chip conveyor	incl.
_	Coolant equipment with ICS 70 bar and paper band filter, tank volume 980 I	incl.
_	Preparation work area mist extraction, flushing and air pistol at set-up station	incl.
_	Walkable working area, pneumatic blow-off device at operator's door	incl.
_	Siemens SINUMERIK 840D sl with 24" multi touch screen	incl.
_	Voltage drop prevention, dual designation, wire identification	incl.
_	Preparation for integration in automation	incl.
_	Remote diagnostics via TeamViewer, Real Time Support incl. mobile device	incl.
_	Delivery, installation and 24 months warranty	incl.

Technical data

Working area			NC rotary table		
X-/Y-/Z-axis	mm	1,000/1,050/1,150	Rotation speed, B-axis	rpm	80
Swing circle diameter	mm	900 (1,300) mm	Loading on pallet	kg	1,500
Loading height on pallet	mm	1,300	Pallet	•	
Rapid traverse, X-/Y-/Z-axis	m/min	70/70/70	Pallet surface (acc. to DIN 55201-A1)	mm	630 x 630
Acceleration, X-/Y-/Z-axis	m/s ²	7/7/7	Tool disc magazine		
Motor spindle			Locations		60
Spindle speed	rpm	8,000	Tool weight	kg	40
Spindle power (40/100 % DC)	kW	66/54	Tool diameter	mm	125 (325)
Spindle torque (40/100 % DC)	Nm	370/300	Tool length	mm	600
Tool taper (acc. to DIN 69893)	HSK-A	100	Control		
			Siemens	type	SINUMERIK 840D sl

Special quotation NBH 630 (D.1009449.001) valid to 2024-05-31; Subject to prior sale.

Payment terms: 30 % deposit, 60 % before delivery, 10 % after commissioning, payable within 30 days; Delivery time on request; Warranty: 24 months; our terms and conditions apply; Technical and price changes reserved. The machine shown here may contain options, accessories and control variants, which are not included in the quotation.