F 90A

Forward vibratory plate



For compaction of asphalt, sand, gravel, rock fill and paving stones.

All our machine models are versatile and easy to operate. They are also durable and reliable, which means lower operating and maintenance costs.

- The Swepac F 90A is a compact, lightweight vibratory plate that is easy to maneuver. It also features a 21 liter built-in water tank.
- The machine is ideal for compacting small asphalted/paved areas and for repair jobs.
- It is also good for gravel and sand. With a Vulkollan® plate (accessory) attached to the base, it can compact paved areas efficiently for an even surface.
- The chassis is hot-dip galvanized, which means superior corrosion protection for the integrated water tank as well.
- The Hardox® wear plate in the base ensures a long service life and the bottom plate is specially designed for asphalt applications.
- Integrated transport wheels can be used to move the machine short distances between jobs.

TECHNICAL DATA	SWEPAC F 90A
Weight, net	108 kg
Base plate, width	560 mm
Height, max / min	1090 / 870 mm
Length, max / min	1110 / 675 mm
Engine	Honda GX 120
Fuel tank capacity	2.5 liter
Fuel	Unleaded or alkylate petrol
Engine output, max	2.9 kW
Centrifugal force	14 kN
Working speed	0 - 25 m/min
Hand/arm vibrations HAV according to ISO 5349 on gravel surface	3.5 m/s^2
Guaranteed sound-power level, L_{WA}	105 dB(A)
Sound pressure level (at operator's ear), OP	90 dB(A)

Part number

202000	F 90A with Honda petrol engine

Accessories

202075	Vulkollan plate complete

F90A_2015-01_GB

Swepac is Sweden's leading manufacturer of soil compactors. The company has a wide range of products, with different motor options and a variety of sizes for every application. Swepac is certified for quality and environmental management under ISO 9001 and 14001, and our machines are Eurotest-certified by SMP Swedish Machinery Testing Institute. You will find detailed information about the company and our products on our website, www.swepac.com. We reserve the right to make changes in technical specifications without prior notice.

Swepac AB
Blockvägen 3 | SE-341 32 Ljungby | Sweden
Tel +46 (0)372-156 00 | www.swepac.com

swepac