

## **FB 280**

## REVERSIBLE VIBRATORY PLATE





- The Swepac FB 280 is a high-performance diesel powered reversible compactor.
- The FB280 has a belt-driven transmission and a fully variable speed control
- Comes with either joystick or handle control
- The Hardox® base plate ensures a long service life.
- With a paving mat (accessory) attached to the base, it compacts paved areas efficiently for an even surface.
- The robust and galvanized protection frame effectively protects the engine against external damage and is equipped with a strong and powerful lifting hook.
- The ergonomics are top class with a de-vibrated control handle (HAV  $< 2.5 \text{ m/s}^2$ ).

## For compaction of sand, gravel, rock fill and paving stones.

All our machine models are versatile and easy to operate. They are also durable and reliable meaning lower operating and maintenance costs.

Weight, net 269 kg Base plate, width x length 550 x 790 mm Height, max / min 1200 / 1030 mm Length, max / min 1530 / 900 mm Engine Hatz 1830 Fuel tank capacity 3,5 liter Fuel Diesel Engine output, max 4,8 kW (6,5 hp) Frequency 81-83 Hz Centrifugal force 40 kN Working speed 0-25 m/min	TECHNICAL DATA – <b>Swepac FB 280</b>	
Height, max / min 1200 / 1030 mm  Length, max / min 1530 / 900 mm  Engine Hatz 1B30  Fuel tank capacity 3,5 liter  Fuel Diesel  Engine output, max 4,8 kW (6,5 hp)  Frequency 81-83 Hz  Centrifugal force 40 kN	Weight, net	269 kg
Length, max / min Engine Hatz 1830 Fuel tank capacity 3,5 liter Fuel Diesel Engine output, max 4,8 kW (6,5 hp) Frequency 81-83 Hz Centrifugal force 40 kN	Base plate, width x length	550 x 790 mm
Engine Hatz 1830 Fuel tank capacity 3,5 liter Fuel Diesel Engine output, max 4,8 kW (6,5 hp) Frequency 81-83 Hz Centrifugal force 40 kN	Height, max / min	1200 / 1030 mm
Fuel tank capacity 3,5 liter Fuel Diesel Engine output, max 4,8 kW (6,5 hp) Frequency 81-83 Hz Centrifugal force 40 kN	Length, max / min	1530 / 900 mm
FuelDieselEngine output, max4,8 kW (6,5 hp)Frequency81-83 HzCentrifugal force40 kN	Engine	Hatz 1B30
Engine output, max 4,8 kW (6,5 hp) Frequency 81-83 Hz Centrifugal force 40 kN	Fuel tank capacity	3,5 liter
Frequency 81-83 Hz Centrifugal force 40 kN	Fuel	Diesel
Centrifugal force 40 kN	Engine output, max	4,8 kW (6,5 hp)
	Frequency	81-83 Hz
Working speed 0–25 m/min	Centrifugal force	40 kN
	Working speed	0-25 m/min

Hand/arm vibrations HAV according to ISO 5349 on gravel surface	< 2,5 m/s <sup>2</sup>
Guaranteed sound-power level, LwA	108 dB(A)
Sound pressure level (at operator's ear), OP	95 dB(A)

PART NUMBER	
308660	FB280 Handle control
308850	FB280 Joystick control

	ACCESSORIES
309092	Handle heating for joystick controlled FB280
303139	Paving mat with brackets