



Fleetcool™ EX

Heavy-Duty Hybrid Coolant

Proven Performance:

- Fully formulated to meet ASTM D6210, ASTM D3306, TMC 329, Cummins CES14603 and CES14439
- Approved for use in Detroit Diesel engines
- Phosphate-free coolant engineered with nitrite and molybdate for unmatched liner pitting protection

Valuable Versatility:

- Offered in ethylene glycol
- Available in 50/50 (RTU) or Concentrate (Full Strength)
- Recommended for use in heavy-duty and high-horsepower applications powered by diesel

Simple Serviceability:

- Provides up to 1,000,000 mile (20,000 hours) of use
- Maintain with liquid DCA-2 or chemically active water filters as needed



Fleetcool EX	EX EG Concentrate	EX EG PreMix
Bulk	CC2739	CC2743
55 Gallon Drum (208 L)	CC2741	CC2745
(3) 1 Gallon Bottle (3.78 L)	CC2742, CC2742X (Canada Only)	CC2746, CC2746X (Canada Only)
275 Gallon Plastic Tote (1040 L)	CC2739USR	CC2743USR

Fleetguard coolant part numbers apply to both U.S. and Canada, except where separate part numbers are noted.

Specification	Performance Standard	EG Concentrate	EG Premix 50/50
Color	Visual	Fuchsia	Fuchsia
Specific Gravity @ 60° F (15.56°C) @ 68° F (20° C)	D1122 D1122	1.12	1.072 1.070
Density	–	9.34 lb/gal (1.12 kg/L)	8.944 lb/gal (1.072 kg/L)
pH (undiluted)	D1287	10.5	10.0
Reserve Alkalinity Typical (undiluted)	D1121	6.1	3.0
Freeze Point (undiluted)	D1177	8° F (-13.33°C) min.	-35.8°F (-37.68°C) min.
Boiling Point (undiluted)	D1120	330° F (165.56°C)	226° F (107.78°C)
Water by Weight (approx.)	D1123	4.0%	48.99% max.
Total Glycol by Weight	–	95.0% min.	50.19% min.
Glassware Corrosion Test	D1384	Pass	Pass
Water Pump Cavitation Test	D2809	Pass	Pass
Aluminum Corrosion Test	D4340	Pass	Pass
Simulated Service Test	D2570	Pass	Pass
Chloride by Weight	D5827	< 25 ppm	< 25 ppm

Check out our “How to Use Fleetguard 3-Way Coolant Test Strips” <https://bit.ly/2vPOBN3>

Monitor Your Cooling System

These quick and accurate tools are all you need:

- Dip and read test strips to easily test your coolant and water
 - Test freeze point and additive levels (CC2602)
 - Test water quality and coolant condition (CC2609 & CC2718)
- Supplemental Coolant Additives (SCAs) to ensure maximum coolant life
 - Re-inhibit as needed using DCA2 technology (WF2131 & DCA30L)
- Refractometers (CC2806) that easily determine freeze point
- Monitor™ Coolant Analysis (CC2700 & CC2706) for when more detailed analysis is required – recommended 1x / year

CC2602



WF2131



DCA30L



CC2700

