



DIESEL 15000 TA XL - STAND BY

PORTABLE POWER

GENERATING SET Range DIESEL

PRODUCT ADVANTAGES

- Generating set guaranteed 3 years
- KOHLER air-cooled industrial engine
- Electric starter with batteries without maintenance
- Connection interface equipped with an hour meter
- Large Autonomy

The APM202 control panel displays overspeed, starting failure, oil pressure, battery and temperature OIL SAFETY Thanks to this functionality, the engine will not start or will stop during its functioning if the oil level for gasolines or the oil pressure for diesels is too low : your generating set is perfectly protected !

Range DIESEL

Both long run times and very long life for professional applications.



DIESEL 15000 TA XL - STAND BY

GENERAL SPECIFICATIONS

| | |
|--|-------------|
| Range | DIESEL |
| Frequency (Hz) | 50 Hz |
| Max power (kW) * | 10 |
| Max power (kVA) | 12.50 |
| Nominal voltage (V) | 400 |
| Number of Phase | Three phase |
| Fuel | Diesel Fuel |
| Tank (L) | 35 |
| 75% cons. (l/h) * | 2.10 |
| 75% Autonomy (h) * | 16.70 |
| Sound power level guaranteed LwA dB(A) | 109 |
| Acoustic pressure level @1m in dB(A) | 95 |
| Acoustic pressure level @7m in dB(A) | 80 |

ENGINE SPECIFICATIONS

| | |
|---|---------------|
| Engine brand | KOHLER |
| Engine ref. | KD425-2 |
| Engine Type | Diesel O.H.V. |
| Start | Electrical |
| Oil shutdown | Oui |
| Displacement (cm3) | 851 |
| Oil system capacity including filters (l) | 2.60 |

ALTERNATOR SPECIFICATIONS

| | |
|--------------------------|------------------|
| Technology | Collar and brush |
| AVR Regulation | No |
| Indication of protection | IP 23 |
| Insulation class | H |

PLUGS AND PANEL DESCRIPTIVE


1 230V 10/16A socket - circuit breaker + 1 230V 16A socket - circuit breaker + 1 400V 16A socket - circuit breaker + hour meter + indicator + APM202

DIMENSIONS AND WEIGHT

| | |
|-----------------|-------|
| Length (cm) | 89.50 |
| Width (cm) | 57 |
| Height (cm) | 77 |
| Dry Weight (kg) | 169 |

PACKAGING

| | |
|------------------------------------|--------------|
| Packaging type | Box / Pallet |
| Length (cm) | 91 |
| Width (cm) | 58.50 |
| Height (cm) | 92 |
| Weight (kg) | 182 |
| Pallet type | |
| Number of box by pallet | 0 |
| Pallet height (cm) | 0 |
| weight of the packaged Pallet (kg) | 0 |



3/15/2022

DIESEL 15000 TA XL - STAND BY - PORTABLE POWER - GENERATING SET DIESEL

This document is not contractual - The SDMO company reserves the right to modify any of the characteristics stated in this document without notice, in a constant effort to improve the quality of its products. *ISO 8528.

SDMO Industries - 270 rue de Kerervern - CS 40047 - 29801 Brest cedex 9 – France - Tél. +33 (0)2 98 41 41 41 - www.kohlersdmo.com

ACCESSORIES SUPPLIED



User and maintenance manual

OPTIONS



R03B

This set includes a differential switch, a hour meter, the plugs and a thermal circuit breaker.



RSTART2

Remote control in order to start or stop the generating set until a distance of 50 meters (needs the APM202 control panel)



VERS050

Switches over automatically if the mains fails, 40A or 100A 1P or if the mains fails, 25A or 40A 3P (needs the installation of a APM202 control panel). Includes the battery charger.



RKDS3

Maintenance kit for KOHLER KD425-2 engine.



RAP

The adaptor for industrial sockets is used to connect 230-V appliances to the industrial socket.



RH2

Cover for SDMO 's generating sets, welding sets and water pumps



RPM

Male plugs for all models made up of : 2 x 16 A/230 V, EEC17: 1 x 16A/230 V, 1 x 32A/230 V and 1 x 16A/400V