KOHLER



DIESEL 6500 TA XL C5

PORTABLE POWER

GENERATING SET Range DIESEL

PRODUCT ADVANTAGES

- · Generating set guaranteed 3 years
- KOHLER air-cooled industrial engine •
- Large Autonomy •
- Connection interface equipped with an hour meter and the APM202 control unit · Electric starter with batteries without

maintenance

GENERATOR SMART CARE is a Bluetooth box which can be used on all the brand's portable generators TECHNOLOGY EQUIPPED WITH AN INNOVATIVE APPLICATION Generator Smart Care is a digital solution which provides access to:- The list of generators- The maintenance due dates- A maintenance aid- The map of reseller partners STAGE V (2016/1628 EU) : This product is compliant with regulation for implementing requirements relating to gaseous and pollutant emission limits in Europe

Range DIESEL

Both long run times and very long life for professional applications.



DIESEL 6500 TA XL C5

GENERAL SPECIFICATIONS

Range	DIESEL	
Frequency (Hz)	50 Hz	
Max power (kW) *	5.20	
Max power (kVA)	6.50	
Nominal voltage (V)	400	
Number of Phase	Three phase	
Fuel	Diesel Fuel	
Tank (L)	16	
75% cons. (l/h) *	1.20	
75% Autonomy (h) *	13.30	
Sound power level guaranteed LwA dB(A)	108	
Acoustic pressure level @1m in dB(A)	93	
Acoustic pressure level @7m in dB(A)	79	

ENGINE SPECIFICATIONS

Engine brand	KOHLER
Engine ref.	KD15-440E_C5
Engine Type	Diesel O.H.V.
Start	Electrical
Oil shutdown	Oui
Displacement (cm3)	442
Oil system capacity including filters (I)	1.50

ALTERNATOR SPECIFICATIONS

Technology	Collar and brush
AVR Regulation	No
Indication of protection	IP 23
Insulation class	Н

PLUGS AND PANEL DESCRIPTIVE

1 230V 10/16A socket - circuit breaker + 1 400V 16A socket - circuit breaker + indicator + APM202

DIMENSIONS AND WEIGHT

Length (cm)	81
Width (cm)	55.50
Height (cm)	59
Dry Weight (kg)	108

PACKAGING

Packaging type	Box
Length (cm)	82
Width (cm)	56.50
Height (cm)	60
Weight (kg)	111
Pallet type	120/80
Number of box by pallet	6
Pallet height (cm)	193
weight of the packaged Pallet (kg)	676



DIESEL 6500 TA XL C5 - PORTABLE POWER - GENERATING SET DIESEL

This document is not contractual - The SDMO company reserves the right to modify any of the characteristics stated in this document without notice, in a constant effort to improve the quality of its products. *ISO 8528.

SDMO Industries - 270 rue de Kerervern - CS 40047 - 29801 Brest cedex 9 - France - Tél. +33 (0)2 98 41 41 41 - www.kohlersdmo.com

This product meets the Qualigen charter, which aims to e level of quality and guarantee the safety of users. Qualig commitment to safety and quality.



DIESEL 6500 TA XL C5 - PORTABLE POWER - GENERATING SET DIESEL This document is not contractual - The SDMO company reserves the right to modify any of the characteristics stated in this document without notice, in a constant effort to improve the quality of its products. *ISO 8528. SDMO Industries - 270 rue de Kerervern - CS 40047 - 29801 Brest cedex 9 – France - Tél. +33 (0)2 98 41 41 41 - www.kohlersdmo.com



DIESEL 6500 TA XL C5

ACCESSORIES SUPPLIED						
	User and maintenance manual			Floor maintaining slot		
OPTIONS	Ergonomic handle grip			Battery without maintenance		
OPTIONS						
	R03	This set includ	es the hour meter and the diffe	rential circuit breaker.		
	RSTART2	Remote control in order to start or stop the generating set until a distance of 50 meters (needs the APM202 control panel)				
	VERSO50	Switches over automatically if the mains fails, 40A or 100A 1P or if the mains fails, 25A or 40A 3P (needs the installation of a APM202 control panel). Includes the battery charger.				
AON	RKB1HD	Trolley kit for the generating sets of 6kW or below				
	RKDS4	Maintenance kit for KOHLER CH350E and CH440E engines (Diesel 6000 E XL C - Diesel 6500 TE XL C).				
	RPM	Male plugs for all models made up of : 2 x 16 A/230 V, EEC17: 1 x 16A/230 V, 1 x 32A/230 V and 1 x 16A/400V				
6	RPQ	For earthing your generator set. Galvanised 1 m long spike, supplied with 2 m of 10 mm ² cable.				



DIESEL 6500 TA XL C5 - PORTABLE POWER - GENERATING SET DIESEL This document is not contractual - The SDMO company reserves the right to modify any of the characteristics stated in this document without notice, in a constant effort to improve the quality of its products. *ISO 8528. SDMO Industries - 270 rue de Kerervern - CS 40047 - 29801 Brest cedex 9 - France - Tél. +33 (0)2 98 41 41 41 - www.kohlersdmo.com