




# QSK38-G3

EPA Tier 2



## Description

The QSK38 is a V-12 cylinder engine with a 38-litre displacement. This Quantum series utilizes sophisticated electronics and premium engineering to provide outstanding performance levels, reliability, and versatility for Standby, Prime and Continuous Power applications.

ISO 9001	This product was manufactured in a facility whose quality management system is certified to ISO 9001 and its Health Safety Environmental Management Systems certified to ISO 14001 and ISO 45001.
ISO 14001	
ISO 45001	
RoHS	Consult factory for RoHS information.

## Features

**High pressure fuel pump, Modular Common Rail Fuel System (MCRS)** and state of the art integrated electronic control system provide superior performance, efficiency, and diagnostics. The electronic fuel pumps deliver up to 1600 bar injection pressure and eliminate mechanical linkage adjustments. The MCRS fuel system utilizes an electric priming pump which is integrated with the off-engine stage-1 fuel filter head and is controlled and powered by the engine ECM. The stage-2 fuel filters are mounted on-engine

**CTT (Cummins Turbo Technologies) HX82/HX83/HE851 turbocharging** utilizes exhaust energy with greater efficiency for improved emissions and fuel consumption.

**Low Temperature After-cooling - Two-pump Two-loop (2P2L)**

**Ferrous Cast Ductile Iron (FCD) Pistons -** High strength design delivers superior durability.

**G-Drive Integrated Design -** Each component has been specifically developed and rigorously tested for G-Drive products, ensuring high performance, durability, and reliability.

**Service and Support -** G-Drive products are backed by an uncompromising level of technical support and after sales service, delivered through a world class service network.

## 1500 rpm (50 Hz Ratings)

Gross engine output			Net engine output			Typical generator set output					
Standby	Prime	Base	Standby	Prime	Base	Standby (ESP)		Prime (PRP)		Base (COP)	
kWm/BHP			kWm/BHP			kWe	kVA	kWe	kVA	kWe	kVA
1223/1640	1107/1484	895/1200	1172/1572	1069/1434	857/1149	1120	1400	1021	1276	818	1023

## General Engine Data

Fuel Rating	FR6788
Type	4 cycle, turbocharged, After-cooled
Bore mm	159
Stroke mm	159
Displacement litre	37.7
Cylinder block	Cast iron, 12 cylinder
Battery charging alternator	55 amps
Starting voltage	24-volt, negative ground
Fuel system	Cummins direct injection MCRS
Fuel filter	Spin-on fuel filters with water separator
Lube oil filter type(s)	Spin-on full flow filter
Lube oil capacity (l)	170
Flywheel dimensions	SAE 0

## Coolpac Performance Data

Cooling system design	2 pump - 2 loop
Coolant ratio	50% ethylene glycol; 50% water
Coolant capacity (l)	Engine only – not applicable
Limiting ambient temp.** (°C)	
Fan power (kWm)	
Cooling system air flow (m³/s)**	
Air cleaner type	Dry replaceable element with restriction indicator

## Fuel Consumption 1500 (50 Hz)

%	kWm	BHP	L/hr	US Gal./hr
<b>Standby Power</b>				
100	1223	1640	296	78.2
<b>Prime Power</b>				
100	1107	1484	265	70.0
75	830	1113	204	54.0
50	554	742	147	38.8
25	277	371	80	21.2
<b>Continuous Power</b>				
100	895	1200	215	56.8

## Weights and Dimensions (Engine only)

Length mm	Width mm	Height mm	Weight (dry) kg
2081	1492	1866	3825

## Ratings Definitions

Emergency Standby Power (ESP):	Limited-Time Running Power (LTP):	Prime Power (PRP):	Base Load (Continuous) Power (COP):
Applicable for supplying power continuously to varying electrical loads for the duration of power interruption of a reliable utility source. Emergency Standby Power (ESP) is in accordance with ISO 8528 and ISO 3046-1, obtained and corrected in accordance with ISO 15550).	Applicable for supplying power to a constant electrical load for limited hours. Limited-Time Running Power (LTP) is in accordance with ISO 8528.	Applicable for supplying power to varying electrical load for unlimited hours. Prime Power (PRP) is in accordance with ISO 8528. Ten percent overload capability is available in accordance with ISO 3046-1. Data shown above represents gross engine performance and capabilities as per ISO 3046-1, obtained and corrected in accordance with ISO 15550.	Applicable for supplying power continuously to a constant load up to the full output rating for unlimited hours. No sustained overload capability is available for this rating. Consult authorized distributor for rating. (Equivalent to Continuous Power in accordance with ISO 8528 and ISO 3046-1, obtained and corrected in accordance with ISO 15550).

For more information contact your local Cummins distributor  
or visit [cummins.com](https://cummins.com)

**Our energy working for you.™**

