



Specifications OctoControl

17-06-2024

ARTICLE NUMBER

60208010	OctoControl Gateway
60208015	OctoControl Basic
60208025	OctoControl Pro
60208030	OctoControl Pro 4G

MAIN SPECIFICATIONS

Input voltage	8 - 32 V
Power consumption	< 100 mA @ 12 V
Operation temperature	- 20 °C to + 40 °C
Storage temperature	-40..80 °C, Relative humidity in operation/ storage up to 95% non-condensing
System communication	WhisperConnect
Weight (kg)	< 0.5
Installation advice	For interior use

OCTOCONTROL GATEWAY SPECIFICATIONS

60208010	OctoControl Gateway
Dimensions (h x w x d) (mm)	140 x 110 x 42
System support	Up to 3 WhisperPower devices
Cloud integration	Yes
Cloud connection	Builtin 4G

OCTOCONTROL BASIC SPECIFICATIONS

60208015	OctoControl Basic
Dimensions (h x w x d) (mm)	140 x 170 x 42
System support	Complete WhisperPower systems
MFD integration	Yes
MFD brands supported	Raymarine, Garmin, Simrad, B&G, Furuno
MFD connection	Ethernet

OCTOCONTROL PRO SPECIFICATIONS

60208025	OctoControl Pro
Dimensions (h x w x d) (mm)	140 x 170 x 42
System support	Complete WhisperPower systems
Cloud integration	Yes
Cloud connection	Builtin 4G **, Ethernet
OctoView support	Yes
OctoView connection	HDMI, USB

MFD integration

MFD brands supported

MFD connection

Yes

Raymarine, Garmin, Simrad, B&G, Furuno

Ethernet