



Specifications

OctoControl

17-06-2024

ARTICLE NUMBER

60208010
60208015
60208025
60208030

OctoControl Gateway
OctoControl Basic
OctoControl Pro
OctoControl Pro 4G

MAIN SPECIFICATIONS

| | |
|-----------------------|--|
| Input voltage | 8 - 32 V |
| Power consumption | < 100 mA @ 12 V |
| Operation temperature | - 20 °C to + 40 °C |
| Storage temperature | -40..80 °C, Relative humidity in operation/ storage up to 95% non-condensing |
| System communication | WhisperConnect |
| Weight (kg) | < 0.5 |
| Installation advice | For interior use |

OCTOCONTROL GATEWAY SPECIFICATIONS

| | |
|-----------------------------|------------------------------|
| 60208010 | OctoControl Gateway |
| Dimensions (h x w x d) (mm) | 140 x 110 x 42 |
| System support | Up to 3 WhisperPower devices |
| Cloud integration | Yes |
| Cloud connection | Built-in 4G |

OCTOCONTROL BASIC SPECIFICATIONS

| | |
|-----------------------------|--|
| 60208015 | OctoControl Basic |
| Dimensions (h x w x d) (mm) | 140 x 170 x 42 |
| System support | Complete WhisperPower systems |
| MFD integration | Yes |
| MFD brands supported | Raymarine, Garmin, Simrad, B&G, Furuno |
| MFD connection | Ethernet |

OCTOCONTROL PRO SPECIFICATIONS

| | |
|-----------------------------|-------------------------------|
| 60208025 | OctoControl Pro |
| Dimensions (h x w x d) (mm) | 140 x 170 x 42 |
| System support | Complete WhisperPower systems |
| Cloud integration | Yes |
| Cloud connection | Built-in 4G **, Ethernet |
| OctoView support | Yes |
| OctoView connection | HDMI, USB |

MFD integration

Yes

MFD brands supported

Raymarine, Garmin, Simrad, B&G, Furuno

MFD connection

Ethernet